

# TECHNICAL SHEET - JACKET P125/3BC



## EUROPEAN STANDARDS

EN 342: 2.3 Protective clothing against cold up to -5° C

## PPE DESCRIPTION

- Model with or without hood.
- When without a hood, with a mesh collar.
- Knitted cuffs.
- 2 padded lower pockets.
- Thermal insulation and lining.
- Maintains temperature in humid environments.
- 1 3M reflective tape

## PACKAGING

Cardboard box

## ALLERGIES

Model with anti-allergy finish

## STORAGE INSTRUCTIONS

Store in a dry place. Protect from exposure to UV rays. Outside of the original packaging, it can be suspended on a hanger.

## PERFORMANCE LEVELS

Tear resistance of the outer fabric	X
Evaporative resistance RET	Class 3
Air permeability (ISO 9237)	Class 2
Resistance to water penetration	X
Icler thermal insulation	0.254 m <sup>2</sup> K/W (B)

## PPE COMPOSITION

- Outer fabric: 100% Polyamide 62 gr/m<sup>2</sup>
- Lining: 100% polyester 62 gr/m<sup>2</sup>
- Mesh: 100% acrylic fiber.
- Thermal insulation: 100% polyester 140 gr/m<sup>2</sup>.

## Colors:



## INSTRUCTIONS FOR USE

Keep PPE closed when in use. The conservation label must not be removed. Respect the cleaning instructions on the label attached to the PPE. Failure to follow cleaning instructions can significantly shorten the life of the PPE. PPE must be kept in a good state of cleanliness and conservation. PPE is permeable to water.

Protection Limits EN342:2004/AC:2008		Activity Light	Activity Moderate
Exposure Time	8 hours	+ 6.00°C	- 10°C
	1 hour	- 16°C	- 22°C

Sizes:



XS	S	M	L	XL	XXL	XXXL
75-85	85-95	95-105	105-115	115-125	125-135	135-145
156-164	164-172	164-172	172-180	180-188	180-188	188-196
60-70	70-80	80-90	90-100	100-110	110-120	120-130

Copyright ©Refrigue Lda.- All rights reserved.

This document is the strict property of Refrigue Lda. It can only be used by the intended recipient in the original form in which it was sent. Any alteration to this document or its annexes will be considered a document forgery, which exposes the recipient to criminal prosecution.



Parque Industrial das Carrascas,  
E.N. 252 ao KM 11, 33  
2950-402 Palmela

(+351) 212 363 601

info@refrigue.pt  
orders@refrigue.pt

refrigue.pt

@refrigue