

# TECHNICAL SHEET - PANTS P127



## EUROPEAN STANDARDS

EN 342 CAT II  
Cold protective clothing for temperatures below -5° C  
EN340  
Protective clothing – General requirements EU Type  
Examination No. 0072/282/162/06/97/0162

## PPE DESCRIPTION

- Elastic waistband to adjust to the body and prevent cold air from entering
- Front zipper with spring
- Elastic adapted to the ankles for perfect fit
- Thermal insulation and lining
- Maintains temperature in humid environments
- Resistant, breathable, easy to maintain

## PACKAGING

Cardboard box

## ALLERGIES

Model with anti-allergy finish

## STORAGE INSTRUCTIONS

Store in a dry place. Protect from exposure to UV rays. Outside of the original packaging, it can be suspended on a hanger.

## Sizes:

XS	s	m	l	xl	xxl	xxxl
75-85	85-95	95-105	105-115	115-125	125-135	135-145
156-164	164-172	164-172	172-180	180-188	180-188	188-196
60-70	70-80	80-90	90-100	100-110	110-120	120-130

## PERFORMANCE LEVELS:

Tear resistance of the outer fabric	X
Evaporative resistance RET	Class 3
Air permeability (ISO 9237)	Class 2
Resistance to water penetration	X
Icler thermal insulation	0.270 m <sup>2</sup> K/W (B)

## PPE COMPOSITION

- Outer fabric 100% nylon 62 gr/m<sup>2</sup> 100%
- Lining polyester 62 gr/m<sup>2</sup> 100%
- Thermal insulation polyester 140 gr/m<sup>2</sup>

## Colors



## INSTRUCTIONS FOR USE

Keep PPE closed when in use. The conservation label must not be removed. Respect the cleaning instructions on the label attached to the PPE. Failure to follow cleaning instructions can significantly shorten the life of the PPE. PPE must be kept in a good state of cleanliness and conservation. PPE is permeable to water.

Protection Limits EN342:2004/AC:2008		Activity Light	Activity Moderate
Exposure Time	8 hours	+ 5°C	- 12°C
	1 hour	- 18°C	- 24°C



Parque Industrial das Carrascas,  
E.N. 252 ao KM 11, 33  
2950-402 Palmela

(+351) 212 363 601

info@refrigue.pt  
orders@refrigue.pt

refrigue.pt

@refrigue