

# TECHNICAL SHEET - VEST P14/3



## EUROPEAN STANDARDS

### EN 14058:2017

Protective clothing against cold environments up to -5°C

### EN ISO 13688:2013

Protective clothing – General requirements EU Type Examination (Module B) no.048/2019

## PERFORMANCE LEVELS

(tested on a size L model) Thermal resistance  $R_{ct}$   
Air permeability  
Thermal insulation  $I_{cler}$

Class 4  
Class 2  
0.174 m<sup>2</sup> K/W (B)

## PPE COMPOSITION

- Outer fabric 100% polyester + PU 100%
- Lining polyester 62 gr/m<sup>two</sup>
- Thermal insulation 100% polyester 200 g/m<sup>two</sup>

## Colors



## Sizes XS - 3XL

## INSTRUCTIONS FOR USE

Keep PPE closed when in use. The conservation label must not be removed. Respect the cleaning instructions on the label attached to the PPE. Failure to follow cleaning instructions can significantly shorten the life of the PPE. PPE must be kept in a good state of cleanliness and conservation. PPE is permeable to water.

## WASHING INSTRUCTIONS

Maximum washing temperature 40°C (normal process). Bleaching is not permitted. Do not tumble dry. Do not iron. Do not dry clean.

## PPE DESCRIPTION

- close model with 3 buttons
- Two padded lower pockets
- Thermal insulation and lining
- Maintains temperature in humid environments
- Resistant, breathable, easy to maintain

## PACKAGING

Cardboard box

## ALLERGIES

Model with anti-allergy finish

## STORAGE INSTRUCTIONS

Store in a dry place. Protect from exposure to UV rays. Outside of the original packaging, it can be suspended on a hanger.



| Sizes  |  | xs      | s       | m       | l       | xl      | xxl     | xxxl    |
|--------|--|---------|---------|---------|---------|---------|---------|---------|
| Chest  |  | 75-85   | 85-95   | 95-105  | 105-115 | 115-125 | 125-135 | 135-145 |
| Height |  | 156-164 | 164-172 | 164-172 | 172-180 | 180-188 | 180-188 | 188-196 |
| Waist  |  | 60-70   | 70-80   | 80-90   | 90-100  | 100-110 | 110-120 | 120-130 |

Copyright ©Refrigue Lda.- All rights reserved.

This document is the strict property of Refrigue Lda. It can only be used by the intended recipient in the original form in which it was sent. Any alteration to this document or its annexes will be considered a document forgery, which exposes the recipient to criminal prosecution.



Parque Industrial das Carrascas,  
E.N. 252 ao KM 11, 33  
2950-402 Palmela

(+351) 212 363 601

info@refrigue.pt  
orders@refrigue.pt

refrigue.pt

@refrigue