

TECHNICAL SHEET - JACKET P392



EUROPEAN STANDARDS

EN 342:2004 CAT II
Protective clothing against cold environments for temperatures below -5°C

EN ISO 13688:2013
Protective clothing – General requirements EU type examination (Module B) n° 001/2022* *In conjunction with pants P295

PPE DESCRIPTION

- Fur collar
- Front zipper with view and springs
- Elastic back to prevent cold air from entering
- A chest pocket with palette and pen separator
- Two padded lower pockets with flap and snaps
- Mesh cuffs for perfect fit
- Thermal insulation and lining
- Maintains temperature in humid environments
- Resistant, breathable, easy to maintain

PACKAGING

Cardboard box

ALLERGIES

Model with anti-allergy finish

STORAGE INSTRUCTIONS

Store in a dry place. Protect from exposure to UV rays. Outside of the original packaging, it can be suspended on a hanger.

Sizes:

XS	S	M	L	XL	XXL	XXXL
75-85	85-95	95-105	105-115	115-125	125-135	135-145
156-164	164-172	164-172	172-180	180-188	180-188	188-196
60-70	70-80	80-90	90-100	100-110	110-120	120-130

PERFORMANCE LEVELS

Tear resistance of the outer fabric
Evaporative resistance RET
Air permeability (ISO 9237)
Resistance to water penetration
Icler thermal insulation

According to
36 m² PA/W
Class 2
X
0.310 m² K/W (B)

PPE COMPOSITION

- Synthetic fur 100% acrylic fiber 700 gr/m²
- Outer fabric 100% polyamide 6.6 185 gr/m²
- Lining 100% polyester 62 gr/m² 100%
- Thermal insulation polyester 220 gr/m² 100%
- Mesh acrylic fiber

Colors



INSTRUCTIONS FOR USE

Keep PPE closed when in use. The conservation label must not be removed. Respect the cleaning instructions on the label attached to the PPE. Failure to follow cleaning instructions can significantly shorten the life of the PPE. PPE must be kept in a good state of cleanliness and conservation. PPE is permeable to water.

Protection Limits EN342:2004/AC:2008	Activity	
	Light	Moderate
Exposure Time	8 hours	- 3.10°C
	1 hour	- 18.10°C
		- 21.30°C
		- 36°C



Parque Industrial das Carrascas,
E.N. 252 ao KM 11, 33
2950-402 Palmela

(+351) 212 363 601

info@refrigue.pt
orders@refrigue.pt

refrigue.pt

@refrigue