


TECHNICAL SHEET - JACKET P394AV 1RT / 2RT



EUROPEAN STANDARDS

EN 342:2004 CAT II
Protective clothing against cold environments for temperatures below -5°C

EN ISO 13688:2013
Protective clothing - General requirements EU type examination (Module B) n° 001/2022* *In conjunction with pants P297

PPE DESCRIPTION

- Fur collar
 - Front zipper with view and springs
 - Elastic back to prevent cold air from entering
 - A chest pocket with palette and pen separator
 - Two padded lower pockets
 - Mesh cuffs for perfect fit
 - Thermal insulation and lining
 - Maintains temperature in humid environments
 - Resistant, breathable, easy to maintain 1 or 2 3M reflective strips
- High visibility jacket

PACKAGING

Cardboard box

ALLERGIES

Model with anti-allergy finish

STORAGE INSTRUCTIONS

Store in a dry place. Protect from exposure to UV rays. Outside of the original packaging, it can be suspended on a hanger.

Sizes:

XS	S	M	L	XL	XXL	XXXL
75-85	85-95	95-105	105-115	115-125	125-135	135-145
156-164	164-172	164-172	172-180	180-188	180-188	188-196
60-70	70-80	80-90	90-100	100-110	110-120	120-130

PERFORMANCE LEVELS

Tear resistance of the outer fabric
Evaporative resistance RET
Air permeability (ISO 9237)
Resistance to water penetration
Icler thermal insulation

According to
36 m² PA/W
Class 2
X
0.310 m² K/W (B)

PPE COMPOSITION

- Synthetic fur
 - Outer fabric
 - Lining
 - Thermal insulation
 - Mesh
- 100% acrylic fiber 700 gr/m2 100%
polyamide + 100% polyester + PU 100%
polyester 62 gr/m2
100% polyester 220 gr/m2
100% acrylic fiber

Colors



INSTRUCTIONS FOR USE

Keep PPE closed when in use. The conservation label must not be removed. Respect the cleaning instructions on the label attached to the PPE. Failure to follow cleaning instructions can significantly shorten the life of the PPE. PPE must be kept in a good state of cleanliness and conservation. PPE is permeable to water.

Protection Limits EN342:2004/AC:2008	Activity Light	Activity Moderate	
		Exposure Time	Temperature
8 hours	- 3.10°C	- 21.30°C	
1 hour	- 18.10°C	- 36°C	



Copyright ©Refrigue Lda.- All rights reserved.

This document is the strict property of Refrigue Lda. It can only be used by the intended recipient in the original form in which it was sent. Any alteration to this document or its annexes will be considered a document forgery, which exposes the recipient to criminal prosecution.

Parque Industrial das Carrascas,
E.N. 252 ao KM 11, 33
2950-402 Palmela

(+351) 212 363 601

info@refrigue.pt
orders@refrigue.pt

refrigue.pt

@refrigue