

TECHNICAL SHEET - JACKET P55BC



EUROPEAN STANDARDS

EN 342:2004 CAT II
Protective clothing against cold environments for temperatures below -5°C
EN 340 Protective clothing – General requirements EU type examination (Module B) no. 0072/282/162/04/14/0024/EX01 04 14

PPE DESCRIPTION

- Fur collar for thermal comfort
- Front zipper with view and springs
- One inner chest pocket made of metal
- Two large pockets at the waist
- Mesh cuffs for a perfect fit
- Adjustable waist with velcro straps on the back
- Thermal insulation and lining
- Maintains temperature in humid environments
- Resistant, breathable, easy to maintain 1 3M Reflective strip

PACKAGING

Cardboard box

ALLERGIES

Model with anti-allergy finish

STORAGE INSTRUCTIONS

Store in a dry place. Protect from exposure to UV rays. Outside of the original packaging, it can be suspended on a hanger.

PERFORMANCE LEVELS

Tear resistance of the outer fabric
Evaporative resistance RET
Air permeability (ISO 9237)
Resistance to water penetration
Icler thermal insulation

According to
36 m² PA/W
Class 2
X
0.310 m² K/W (B)

PPE COMPOSITION

- Synthetic fur 100% acrylic fiber 700 gr/m²
- Outer fabric 100% polyamide 6.6 185 gr/m²
- Lining 100% polyester 62 gr/m² 100%
- Thermal insulation polyester 220 gr/m² 100%
- Mesh acrylic fiber

Colors



INSTRUCTIONS FOR USE

Keep PPE closed when in use. The conservation label must not be removed. Respect the cleaning instructions on the label attached to the PPE. Failure to follow cleaning instructions can significantly shorten the life of the PPE. PPE must be kept in a good state of cleanliness and conservation. PPE is permeable to water.

| Limites de Protecção EN 342:2004/AC:2008 | | Atividade Ligeira | Atividade Moderada |
|---|---------|----------------------|-----------------------|
| Tempo Exposição | 8 Horas | - 1°C | -19°C |
| | 1 Hora | - 15°C | -32°C |

Sizes:

| XS | S | M | L | XL | XXL | XXXL |
|---------|---------|---------|---------|---------|---------|---------|
| 75-85 | 85-95 | 95-105 | 105-115 | 115-125 | 125-135 | 135-145 |
| 156-164 | 164-172 | 164-172 | 172-180 | 180-188 | 180-188 | 188-196 |
| 60-70 | 70-80 | 80-90 | 90-100 | 100-110 | 110-120 | 120-130 |



Copyright ©Refrigue Lda.- All rights reserved.

This document is the strict property of Refrigue Lda. It can only be used by the intended recipient in the original form in which it was sent. Any alteration to this document or its annexes will be considered a document forgery, which exposes the recipient to criminal prosecution.

Parque Industrial das Carrascas,
E.N. 252 ao KM 11, 33
2950-402 Palmela

(+351) 212 363 601

info@refrigue.pt
orders@refrigue.pt

refrigue.pt

@refrigue