

# TECHNICAL SHEET - JACKET P56



## EUROPEAN STANDARDS

EN 342:2004 CAT II  
Protective clothing against cold environments for temperatures below -5°C  
EN 340 Protective clothing – General requirements EU type examination (Module B) no. 0072/282/162/04/14/0024/EX01 04 14

## PERFORMANCE LEVELS

Tear resistance of the outer fabric  
Evaporative resistance RET  
Air permeability (ISO 9237)  
Resistance to water penetration  
Icler thermal insulation

According to  
36 m<sup>2</sup> PA/W  
Class 2  
X  
0.310 m<sup>2</sup> K/W (B)

## PPE COMPOSITION

- Synthetic fur 100% acrylic fiber 700 gr/m<sup>2</sup>
- Outer fabric 100% polyester + PU
- Lining 100% polyester 62 gr/m<sup>2</sup>
- Thermal insulation 100% polyester 220 gr/m<sup>2</sup>
- Mesh 100% acrylic fiber

## Colors



## PPE DESCRIPTION

- Fur collar for thermal comfort
- Front zipper with view and springs
- One inner chest pocket made of metal
- Two large pockets at the waist
- Mesh cuffs for a perfect fit
- Adjustable waist with velcro straps on the back
- Thermal insulation and lining
- Maintains temperature in humid environments
- Resistant, breathable, easy to maintain

## PACKAGING

Cardboard box

## ALLERGIES

Model with anti-allergy finish

## STORAGE INSTRUCTIONS

Store in a dry place. Protect from exposure to UV rays. Outside of the original packaging, it can be suspended on a hanger.

## INSTRUCTIONS FOR USE

Keep PPE closed when in use. The conservation label must not be removed. Respect the cleaning instructions on the label attached to the PPE. Failure to follow cleaning instructions can significantly shorten the life of the PPE. PPE must be kept in a good state of cleanliness and conservation. PPE is permeable to water.

Protection Limits <b>EN342:2004/AC:2008</b>		Activity Light	Activity Moderate
Exposure Time	8 hours	- 1°C	- 19°C
	1 hour	- 15°C	- 32°C

Sizes:



XS	S	M	L	XL	XXL	XXXL
75-85	85-95	95-105	105-115	115-125	125-135	135-145
156-164	164-172	164-172	172-180	180-188	180-188	188-196
60-70	70-80	80-90	90-100	100-110	110-120	120-130

Copyright ©Refrigue Lda.- All rights reserved.

This document is the strict property of Refrigue Lda. It can only be used by the intended recipient in the original form in which it was sent. Any alteration to this document or its annexes will be considered a document forgery, which exposes the recipient to criminal prosecution.

Parque Industrial das Carrasças,  
E.N. 252 ao KM 11, 33  
2950-402 Palmela

(+351) 212 363 601

info@refrigue.pt  
orders@refrigue.pt

refrigue.pt

@refrigue