

TECHNICAL SPECIFICATIONS - P541 JACK



EUROPEAN STANDARDS

EN 342:2004 CAT II Protective clothing against cold environments for temperatures below -5°C EN 340 Protective clothing – General requirements EU Type Examination (Module B) No. 0072/282/162/04/14/0026

PPE DESCRIPTION

- Easy and quick to put on a Canadian-style blanket
- Hood lined with fur and ribbed knit around the face.

- Adjustable drawstring hood with lock
- Front closure with placket and springs
- A chest pocket with flap and spring
- Two padded front pockets with flap and springs
- Knitted cuffs for a perfect fit
- Adjustable waist with Velcro straps at the back
- Side opening with double zipper, 95 cm
- Thermal insulation and lining
- Maintains temperature in humid environments.
- Durable, breathable, easy to care for

PACKAGING

Cardboard box

ALLERGIES

Model with hypoallergenic finish.

STORAGE INSTRUCTIONS

Store in a dry place. Protect from UV exposure. Outside of its original packaging, it can be hung on a hanger.

PERFORMANCE LEVELS

Tear resistance of the outer fabric.
Evaporative resistance. RET
Air permeability (ISO 9237)
Resistance to water penetration
Thermal insulation Icler

According to
36 m² PA/W
Class 2
X
0.493 m² K/W (B)

PPE COMPOSITION

- Synthetic fur 100% acrylic fiber 700 gr/m²
- Outer fabric 100% polyamide 6.6 185 gr/m²
- Lining 100% polyester 62 gr/m² 100%
- Thermal insulation polyester 220 gr/m² 100%
- Mesh acrylic fiber

Colors



INSTRUCTIONS FOR USE

Keep the PPE closed when in use. Do not remove the care label. Follow the cleaning instructions on the label attached to the PPE. Failure to follow the cleaning instructions may significantly reduce the lifespan of the PPE. The PPE must be kept clean and well-maintained. The PPE is permeable to water.

Protection Limits EN342:2004/AC:2008		Activity Slight	Activity Moderate
Exposure Time	8 Hours	-17.5°C	-42.4°C
	1 Hour	-38.0°C	-62.1°C

Sizes:



XS	S	M	L	XL	XXL	XXXL
75-85	85-95	95-105	105-115	115-125	125-135	135-145
156-164	164-172	164-172	172-180	180-188	180-188	188-196
60-70	70-80	80-90	90-100	100-110	110-120	120-130

Copyright ©Refrigue Ltd.All rights reserved.

This document is the exclusive property of Refrigue Lda. It may only be used by the intended recipient in its original form as sent. Any alteration to this document or its attachments will be considered document forgery, which exposes the recipient to criminal prosecution.



Parque Industrial
das Carrascas,
E.N. 252 ao KM 11, 33
2950-402 Palmela

(+351) 212 363 601

info@refrigue.pt
orders@refrigue.pt

refrigue.pt

@refrigue